





Product Number	Pack Size	Carton Qty.
68480	n/a	1

ABOUT THE PRODUCT

Wynn's Aircomatic® III with ozone generator is designed for removal and prevention of bad odours in air- conditioning systems and vehicle interior with the associated additives.

BENEFITS

Wynn's Aircomatic® III has been designed to provide the following benefits:

- Easy to use, no supervision necessary during treatment
- 02 12V DC cigarette lighter connection





ADVANTAGES

Wynn's Airco-Clean® Ultrasonic (Product No. 30205) and Wynn's Air Purifier (Product No. 31705) into small drops of approximately 5 microns. The vapour of Airco-Clean® is blown towards the evaporator of the air-conditioning by means of a built-in ventilator. The vapour of Air Purifier is nebulized in the interior of the car. Because of the size of the droplets, dismantling of the pollen filter is NOT necessary when applying Wynn's Airco-Clean®.

Wynn's Aircomatic III's outlet tube directs the vapour flow and guarantees the correct size of the droplets. Wynn's Aircomatic III's ozone generator produces ozone during a programmed time. The ozone is blown in the interior of the vehicle by means of a built-in ventilator. The ozone reacts with the molecules that create bad smells and helps to neutralise them in combination with the activity of Wynn's Air Purifier. This leads to optimal removal of bad smells in car interiors and a safe re-entry of the car immediately after the treatment.

DIRECTIONS OF USE

Refer to Wynn's Aircomatic III's operating manual.

APPLICATIONS

Treatment 1: Nebulisation of Wynn's Airco-Clean® Ultrasonic

To stop bad odours in air-conditioning systems of cars, trucks and buses.

Treatment 2: Nebulisation of Wynn's Air Purifier

To stop bad odours in the interior of cars, trucks (also in trunks).

Treatment 3: Generation of ozone (long or short period) followed by nebulisation of Wynn's Air Purifier To stop severe odours in the interior of cars and trucks.

The treatments can be carried out individually or in combination. Airco-Clean® treatments should be carried out once or twice a year or whenever necessary. Air Purifier treatments should be carried out three or four times a year or whenever necessary.